




END & CORNER POST TOP OPTIONS		TOP & BOTTOM FABRIC OPTIONS
STANDARD	DOMED	KNUCKLE
		

FENCE SECTION ELEVATION

- NOTES:
1. METRIC DIMENSIONS ARE NOMINAL EQUIVALENTS TO U.S. DIMENSIONS.
 2. SPECIFICATIONS SHOWN CAN BE CHANGED BY MASTER HALCO ONLY.
 3. FOOTING WIDTH TO BE (4)X POST WIDTH. MINIMUM DEPTH 36" [914MM].
 4. NORMAL FENCE HEIGHTS FOR TENNIS COURTS: 10' [3048MM] OR 12' [3658MM].
 5. BOTTOM RAIL OPTIONAL ON BOTH FENCE HEIGHTS.
 6. MID RAIL USUAL FOR 12' [3658MM] HT & OPTIONAL FOR 10' [3048MM] HT.
 7. OMIT TENSION WIRE IF BOTTOM RAIL IS UTILIZED.
 8. SEE SECTION 02831 (SPECIFICATIONS) FOR DETAILS.

MIN DEPTH
IN: 36"
MM: 914

WIDTH
IN: _____
MM: _____



ANCHOR FENCE PRODUCTS
by Master Halco
Orange, CA
Phone No.: 800-229-5615
www.FenceOnline.com

TYPICAL TENNIS FENCE

SQUARE END POSTS

BY: JRR
DATE: 01-26-96
REV: C
REV DATE: 08-25-06

DWG: 1-1210
LAYER: 1
SCALE: 3/8" = 1'-0"