




END & CORNER POST TOP OPTIONS		TOP & BOTTOM FABRIC OPTION
STANDARD	DOMED	KNUCKLE
		

FENCE SECTION ELEVATION

NOTES:

1. METRIC DIMENSIONS ARE NOMINAL EQUIVALENTS TO U.S. DIMENSIONS.
2. SPECIFICATIONS SHOWN CAN BE CHANGED BY MASTER HALCO ONLY.
3. FOOTING WIDTH TO BE (4)X POST WIDTH. MINIMUM DEPTH 36" [914MM].
4. NORMAL FENCE HEIGHTS FOR TENNIS COURTS: 10' [3048MM] OR 12' [3658MM].
5. BOTTOM RAIL OPTIONAL ON BOTH FENCE HEIGHTS.
6. MID RAIL USUAL FOR 12' [3658MM] HT & OPTIONAL FOR 10' [3048MM] HT.
7. OMIT TENSION WIRE IF BOTTOM RAIL IS UTILIZED.
8. SEE SECTION 02831 (SPECIFICATIONS) FOR DETAILS.



ANCHOR FENCE PRODUCTS
by Master Halco
Orange, CA
Phone No.: 800-229-5615
www.FenceOnline.com

TYPICAL TENNIS FENCE

ROUND END POSTS

BY:	JRR	DWG:	1-1310
DATE:	01-22-96	LAYER:	1
REV:	C	SCALE:	3/8" = 1'-0"
REV DATE:	08-25-06		