

CHAIN LINK FENCE FABRIC SELECTIONS HIGH SECURITY

HEIGHT

Chain link fabric is available in heights of 3 feet (914 mm) through 16 feet (4877 mm).

MESH SIZE

HIGH SECURITY - 2 inch (50 mm) MESH, 6 gauge [0.192”(4.88 mm)] or 1-3/4” (44 mm) MESH,

6 gauge [0.192 ” (4.88 mm)]

Fabric in one piece for full height up to 16 ’-0” (4877 mm).

(See separate specifications for high security and maximum security .)

Standard tolerance for wire diameter is +/- 0.005 inch (0.13 mm).

BREAKLOAD AND CORE WIRE GAUGE

6 gauge [0.192 ”(4.88 mm)] wire diameter with breakload strength of 2170 lbf (9650 N)].

COLORS

ASTM F 934 - Black, Brown, Woodland Green (olive), Ensor Green (green), as selected by architect.
(Special colors available at special cost.)

SELVAGE

Selvage of fabrics to be knuckled on bottom and twisted at top.

BE AWARE OF THE SERIOUS INJURY THAT CAN OCCUR TO ANYONE (INCLUDING CHILD OR ANIMAL) ATTEMPTING TO CRAWL UNDER (OR CLIMB OVER) A FENCE WITH TWISTED SELVAGE.

CHAIN LINK FENCE FABRIC SELECTIONS MAXIMUM SECURITY

HEIGHT

Chain link fabric is available in heights of 3 feet (914 mm) through 16 feet (4877 mm).

MESH SIZE

MAXIMUM SECURITY - 2 inch (50 mm) MESH, 6 gauge [0.192”(4.88 mm)] or 1-3/4 inch (44 mm) MESH,

6 gauge [0.192 ”(4.88 mm)] at bottom and 3/8 inch (9.5 mm) MESH, 11 gauge [0.120” (3.05 mm)] at top

(See high security section.)

Standard tolerance for wire diameter is +/- 0.005 inch (0.13 mm).

BREAKLOAD AND CORE WIRE GAUGE

11 gauge [0.120” (3.05 mm)] wire diameter with breakload strength of 850 lbf (3780 N)].

6 gauge [0.192 ”(4.88 mm)] wire diameter with breakload strength of 2170 lbf (9650 N)].

COLORS

ASTM F 934 - Black, Brown, Woodland Green (olive), Ensor Green (green), as selected by architect.
(Special colors available at special cost.)

SELVAGE

Selvage of 2 inch (50 mm) mesh is knuckled at bottom and twisted at top, 3/8 ” (9.5 mm) mesh is knuckled at top and bottom.